

## Specification Sheet

Part Number: 157-00112

One-piece design allows installers to mount and bundle wire or cables single-handedly.

Fastener delivers high extraction force for reliable performance, yet it's easy to install.

Can be unscrewed or extracted from threaded holes for easy removal and re-usability.



1-Piece Cable Tie/Fir Tree Mount with Disc, 8"L, M6 Threaded Hole, PA66HIRHSUV, Black, 500/bg

Article Number 157-00112

Type T50ROSFTQM6

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton Blind Hole Mount Cable Tie for threaded holes offers an easy-to-use method for bundling and affixing cables. The one-piece mount offers a low insertion force and aggressively resists pull off, for secure attachment to panel holes with thicknesses from 0.02" to 0.28" or threaded blind holes. The disc on top of the mount covers the hole and minimizes ingress of water and debris.

Short Description 1-Piece Cable Tie/Fir Tree Mount with Disc, 8"L, M6 Threaded Hole, PA66HIRHSUV, Black, 500/bg

Global Part Name T50ROSFTQM6-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 222.4

Length L (Imperial) 8.0

Length L (Metric) 203.2

Fixation Method Fir tree for round holes

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 0.20

Width W (Metric) 5.08

Bundle Diameter Min (Imperial) 0.08

Bundle Diameter Min (Metric) 2.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Thickness T (Imperial) 0.06

|                                   |  |
|-----------------------------------|--|
| Thickness T (Metric)              | 1.5  |
| Height H (Imperial)               | 0.54   |
| Height H (Metric)                 | 13.83  |
| Diameter D (Imperial)             | 0.25   |
| Diameter D (Metric)               | 6.0  |
| Panel Thickness Min (Imperial)    | 0.13   |
| Panel Thickness Max (Imperial)    | 0.28   |
| Panel Thickness Min (Metric)      | 3.25   |
| Panel Thickness Max (Metric)      | 7.0  |
| Mounting Hole Diameter D (Metric) | M6   |
| Disc Diameter (Metric)            | 16   |
| Disc Diameter (Imperial)          | 0.31   |
| Material                          | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut                 | PA66HIRHSUV  |
| Flammability                      | UL 94 HB   |

|                              |                                   |
|------------------------------|-----------------------------------|
| UV Resistant (Yes/No)        | Yes                               |
| Use Conditions               | For Indoor and Outdoor Use        |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 500                               |
| Package Quantity (Metric)    | 500                               |
| Customs Number               | 3926909988                        |

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)