

## Specification Sheet

Part Number: 157-00186



The one-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from 0.8mm to 7.0mm or threaded blind holes.

The 'disc' on the top of the fir tree covers the hole and minimises the ingress of water and dirt.

1-Piece Cable Tie/Fir Tree Mount/Disc, 25mm Offset, 9.1"L, 6.1 - 7.0 mm or 6.1 - 6.6 mm (hexagonal) Hole, PA46, Brown, 500/pkg

Article Number 157-00186

Type T50ROSFT6SO25B

Color Brown (BN)

Quantity Per bag

Product Description HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description 1-Piece Cable Tie/Fir Tree Mount/Disc, 25mm Offset, 9.1"L, 6.1 - 7.0 mm or 6.1 - 6.6 mm (hexagonal) Hole, PA46, Brown, 500/pkg

Global Part Name T50ROSFT6SO25B-PA46-BN

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 9.1

Length L (Metric) 230.0

Offset Length (Imperial) 0.98

Offset Length (Metric) 25.0

Fixation Method Fir tree for round holes

Identification Plate Position none

Releasable Closure No

Width W (Imperial) 0.19

Width W (Metric) 5.1

Bundle Diameter Min (Imperial) 0.08

Bundle Diameter Min (Metric) 2.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Height H (Imperial)	0.90
Height H (Metric)	22.30
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.26
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.65
Mounting Hole Diameter D (Imperial)	0.24 - 0.28 ";0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.6 mm (hexagonal) 6.1 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter (Metric)	19.0
Disc Diameter (Imperial)	0.75
Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46

Material Cable Tie	Polyamide 4.6 (PA46)
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +266°F (-40°C to +130°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)