

Specification Sheet

Part Number: 157-00275

Standoff design keeps bundles away from mounting surface and obstructions.

Low-profile outside serrated tie with grip rails keeps harnesses and wires protected and secure.

Four-pawl, three-tooth design provides low insertion force and delivers outstanding stud retention.

Mount can be used in a wide variety of applications including 5 mm and 6 mm bolts, as well as weld studs.

Designed for quick and easy assembly by hand without the need for tools.



1-Piece Cable Tie/Round Stud Mount, M6 stud, 8.0" Long, PA66HIRHS, Black, 1500/pkg

Article Number 157-00275

Type T50RM6OSSM

Color Black (BK)

Quantity Per carton

Product Description One-piece cable tie with stud mount features a standoff design that keeps bundles away from mounting surfaces and obstructions. With its low insertion force and high extraction performance, HellermannTyton's mounting tie offers the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description	1-Piece Cable Tie/Round Stud Mount, M6 stud, 8.0" Long, PA66HIRHS, Black, 1500/pkg
Global Part Name	T50RM6OSSM-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.8
Length L (Metric)	223.52
Fixation Method	Stud Mount
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	1.00
Width W (Metric)	25.0
Bundle Diameter Min (Imperial)	0.2
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	1.97

Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	1.31
Height H (Metric)	33.3
Mounting Hole Diameter D (Metric)	M6
Stud Diameter (Metric)	M6
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial) 1500

Package Quantity (Metric) 1500

Customs Number 3926909988