

Specification Sheet

Part Number: 157-00461



Provides separation between bundles to prevent chafing and abrasion.

High tensile strength of 150 lb suits heavy duty applications.

Straps are releasable for increased serviceability.

1-Pc. Cable Tie w/Screw Mount, 13.1" Long, M8 Hole, 3.3" Max Bundle Dia, PA66HIRHSUV, Black, 800/ctn

Article Number 157-00461

Type WSI8MMB

Color Black (BK)

Quantity Per carton

Product Description These cable ties attach with a screw or bolt to an existing hole, or secure to a stud with a nut. They provide an attachment point for securing and routing a single bundle. The mounts provide the highest level of fastening for critical cable security.

Short Description 1-Pc. Cable Tie w/Screw Mount, 13.1" Long, M8 Hole, 3.3" Max Bundle Dia, PA66HIRHSUV, Black, 800/ctn

Global Part Name WSI8MMB-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)	120
Minimum Tensile Strength (Metric)	535
Length L (Imperial)	13.1
Length L (Metric)	334.0
Fixation Method	Weld Stud Fixing
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.5
Width W (Metric)	12.7
Bundle Diameter Min (Imperial)	0.37
Bundle Diameter Min (Metric)	9.5
Bundle Diameter Max (Imperial)	3.25
Bundle Diameter Max (Metric)	82.6
Thickness T (Imperial)	0.06
Thickness T (Metric)	1.4

Height H (Imperial)	0.19
Height H (Metric)	4.9
Mounting Hole Diameter D (Imperial)	0.33
Mounting Hole Diameter D (Metric)	8.4 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	800
Package Quantity (Metric)	500
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)