

## Specification Sheet

Part Number: 157-00510



Head allows for a 0.2" lateral adjustment on stud during installation.

Quick and easy installation ideal for manufacturing environment.

1-Piece Cable Tie/Oval Stud Mount, Designed for 5.0 - 6.0 mm stud, 6.0" Long, PA66HS, Gray, 3000/ctn

Article Number	157-00510
Type	T50SOSSB5-High-E-C-CC
Color	Gray (GY)
Quantity Per	carton
Product Description	Oval Shaped Stud Mount's special design allows for a 0.2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.
Short Description	1-Piece Cable Tie/Oval Stud Mount, Designed for 5.0 - 6.0 mm stud, 6.0" Long, PA66HS, Gray, 3000/ctn
Global Part Name	T50SOSSB5-High-E-C-CC-PA66HS-GY

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	222.4
Length L (Metric)	167.0
Fixation Method	Stud Mount
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.20
Width W (Metric)	5.0
Bundle Diameter Min (Imperial)	0.04
Bundle Diameter Min (Metric)	1.0
Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0
Stud Length Max (Metric)	14.2
Stud Diameter (Metric)	M6 5.0 mm

Stud Diameter (Imperial)	0.20 ", 0.24
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988