

Specification Sheet

Part Number: 157-04004

Attached cable tie head ensures desired orientation is maintained.

Toolless assembly is fast and easy.

Disc adjusts tie for pressure from various directions and minimizes debris ingress.

Fir tree foot part can be used for a variety of panel thicknesses.



1-Piece Cable Tie/Fir Tree Mount, 9.1" L, 4x Oval Hole Fir Tree, PA66HIRHSUV, Black, 3000/carton

Article Number 157-04004

Type T50ROSFTOVALIL15R

Color Black (BK)

Quantity Per carton

Product Description These cable ties feature a fir tree mount with an innovative four-sided, 360° branch design that interfaces fully, for a wide range of oval hole applications. This industry-first design allows for one part to be used across multiple common hole sizes and delivers cost savings through part consolidation. The clamp rails along the inside of the cable tie strap increase the grip around bundles, reducing the potential for lateral cable bundle movement.

Short Description	1-Piece Cable Tie/Fir Tree Mount, 9.1" L, 4x Oval Hole Fir Tree, PA66HIRHSUV, Black, 3000/carton
Global Part Name	T50ROSFTOVALIL15R-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	9.1
Length L (Metric)	230.3
Fixation Method	Fir Tree for oval holes
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.20
Width W (Metric)	5.1
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0

Height H (Imperial)	0.86
Height H (Metric)	21.8
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.27
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 ";0.26 x 0.49 ";0.26 x 0.51 ";0.28 x 0.47
Mounting Hole Diameter D (Metric)	6.2 x 12.2 mm 6.5 x 13.0 mm 7.0 x 12.0 mm 6.5 x 12.5 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter (Metric)	17.3 x 23.3
Disc Diameter (Imperial)	0.68 x 0.92
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV

Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)