

Specification Sheet

Part Number: 157-04100

This sustainable option in postindustrial recycled material offers the same performance level as our PA66HIRHS products.

The ReSource family of products helps companies meet their sustainability goals.

All-in-one bundling and fastening solution reduces costs and assembly time.

Fir tree provides low insertion effort yet demonstrates high extraction resistance.



1-Piece Cable Tie/Fir Tree Mount w Disc, 6.6"L, 0.25" (hexagonal) or 0.26 - 0.28 " Mounting Hole, PA66HIRHS(REC100), Black, 4000/ctn

Article Number 157-04100

Type T50SOSFT6.5LG-E4

Color Black (BK)

Quantity Per carton

Product Description Part of our sustainable line of products, the ReSource product family features solutions made from excess plastic left over from the manufacturing process or from consumers. This fir tree mount is made from 100 percent postindustrial recycled plastic. It provides a secure grip in a mounting hole. The fir tree provides a low push-in force and high pull-out resistance. The mount can slide along the cable tie to adjust orientation as needed. The mount is sold as an assembly with the cable tie.

Short Description	1-Piece Cable Tie/Fir Tree Mount w Disc, 6.6"L, 0.25" (hexagonal) or 0.26 - 0.28 " Mounting Hole, PA66HIRHS(REC100), Black, 4000/ctn
Global Part Name	T50SOSFT6.5LG-E4-PA66HIRHS(REC100)-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	6.6
Length L (Metric)	167.9
Fixation Method	Fir tree for round holes
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.04
Bundle Diameter Min (Metric)	1.0
Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Height H (Imperial)	0.05
Height H (Metric)	1.3
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.32
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	8.25
Mounting Hole Diameter D (Imperial)	0.25 (hexagonal) ";0.26
Mounting Hole Diameter D (Metric)	6.5 mm 6.35 mm (hexagonal)
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.5
Disc Diameter (Metric)	16.0
Disc Diameter (Imperial)	0.63

Material	Polyamide 6.6 recycled, high impact modified, heat stabilized (PA66HIRHS(REC100))
Material Shortcut	PA66HIRHS(REC100)
Flammability	UL 94 HB
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988