

Specification Sheet

Part Number: 157-04130

Fir Tree Push Mount offers simple and easy to use method of bundling and fixing cable ties.

The design of the fir tree ensures a positive secure fixing into panels with thicknesses from 0.7mm to 3.5mm or threaded blind holes.

The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.



1-Piece Cable Tie/Fir Tree Mount/Disc, 6.3"L, 6.1 - 6.9 mm Mounting Hole, PA66HIRHS, Black, 2000/ctn

Article Number 157-04130

Type T50SOSFT6E3

Color Black (BK)

Quantity Per carton

Product Description One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description 1-Piece Cable Tie/Fir Tree Mount/Disc, 6.3"L, 6.1 - 6.9 mm Mounting Hole, PA66HIRHS, Black, 2000/ctn

Global Part Name T50SOSFT6E3-PA66HIRHS-BK

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 150

Length L (Imperial) 6.34

Length L (Metric) 161.0

Fixation Method Fir tree for round holes

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 0.19

Width W (Metric) 4.7

Bundle Diameter Min (Imperial) 0.04

Bundle Diameter Min (Metric) 1.0

Bundle Diameter Max (Imperial) 1.38

Bundle Diameter Max (Metric) 35.0

Panel Thickness Min (Imperial) 0.03

Panel Thickness Max (Imperial) 0.14

Panel Thickness Min (Metric) 0.7

Panel Thickness Max (Metric) 3.5

Mounting Hole Diameter D (Imperial) 0.24 " - 0.27

Mounting Hole Diameter D (Metric) 6.1 - 6.9 mm

Mounting Hole Diameter D Max (Metric) 6.9

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Use Conditions For Indoor and Outdoor Use

ROHS Compliant Yes

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

