

Specification Sheet

Part Number: 157-04147

One-piece design eliminates the need for multiple components, saving you time and hassle.

Downward tie orientation routes cables below the mounting surface.

High-quality materials and robust design ensure a secure and reliable retention of cables.

Specifically designed to fit M5 and M6 studs, making them perfect for a wide range of automotive applications.



Offset M5/T5/M6 Stud Mount Tie, B-Series, 8.8" L, 50 lb Tensile Strength, PA66HIRHSUV, Blk, 2000/carton

Article Number 157-04147

Type T50ROSM6SMSO25B

Color Black (BK)

Quantity Per carton

Product Description One-piece cable tie with offset stud mount positions bundles away from obstructions, heat or sources of abrasion. With its low push-on force and high pull-off strength, this mounting tie offers the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description	Offset M5/T5/M6 Stud Mount Tie, B-Series, 8.8" L, 50 lb Tensile Strength, PA66HIRHSUV, Blk, 2000/carton
Global Part Name	T50ROSM6SMSO25B-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.8
Length L (Metric)	224.0
Offset Length (Imperial)	1.0
Offset Length (Metric)	25.5
Fixation Method	Weld Stud Fixing
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.19
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0

Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.35
Height H (Imperial)	0.59
Height H (Metric)	15.0
Mounting Hole Diameter D (Imperial)	0.20 x 0.03 "; 0.24 x 0.04 "; 0.20
Mounting Hole Diameter D (Metric)	T5 M6 x 1 M5 x 0.8
Mounting Hole Diameter D Min (Imperial)	0.2
Mounting Hole Diameter D Max (Imperial)	0.24
Mounting Hole Diameter D Max (Metric)	6.0
Stud Diameter (Metric)	5.0 mm 6.0 mm
Stud Diameter (Imperial)	0.20 ", 0.24
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV

UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	2000
Package Quantity (Metric)	2000
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)