HellermannTyton

Specification Sheet

Part Number: 2N0M



Sheathing allows flexible routing and lead-out of cables The inner edges are beveled preventing damage to cables Sheathing is reusable and resistant to most chemicals Spiralwrap is U.L. Recognized

Spiralwrap Protective Sheathing, 0.25" Diameter, PA6, Black, 1000ft/roll

Article Number

161-05033

Туре

2N

Color Black (BK)

Quantity Per

reel

Product Description	HellermannTyton Spiralwrap provides an effective means for routing and securing wires around corners and bends, and helps keep wires out of pinch points within moving panel doors. Spiralwrap is installed using a gapped or butted installation which impacts harnesses flexibility, wire coverage and abrasion resistance. A gapped installation leaves space between the sheathing to accommodate breakouts and adds flexibility to the harness. A butted installation wraps tightly around the bundle to provide greater abrasion resistance and add rigidity. Natural PA6 nylon material is recommended for use within enclosed environments where possibility of fire exists. Black PA6 nylon material is suitable for outdoor applications and can be used in direct sunlight for extended periods of time.
Short Description	Spiralwrap Protective Sheathing, 0.25" Diameter, PA6, Black, 1000ft/roll
Global Part Name	2N-PA6-BK
Length L (Imperial)	1000.0
Length L (Metric)	304.8
Variant	Spiral Binding
Bundle Diameter Min (Imperial)	0.19
Bundle Diameter Min (Metric)	4.75
Bundle Diameter Max (Imperial)	2
Bundle Diameter Max (Metric)	50.8
Diameter D (Imperial)	0.25
Diameter D (Metric)	5.1

Nominal Diameter (Imperial)	0.25
Nominal Diameter (Metric)	6.35
Wall Thickness WT (Imperial)	.025
Wall Thickness WT (Metric)	0.64
Material	Polyamide 6 (PA6)
Material Shortcut	540
	PA6
Flammability	PA6 UL 94 HB
Flammability	UL 94 HB
Flammability UV Resistant (Yes/No)	UL 94 HB No
Flammability UV Resistant (Yes/No) Use Conditions	UL 94 HB No For Indoor Use Only

Package Quantity (Imperial) 1000

Package Quantity (Metric) 304.8

Customs Number

3926909988

© 2024 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions