## **HellermannTyton**

## **Specification Sheet**

Part Number: 167-00219

Living hinge allows harness serviceability and reduces assembly time.


Internal ribs affix to exterior of tubing which prevents slipping during tension or movement.

Snap-on connection makes installations quick and easy and increases efficiencies in harness assembly.

Junction point outlets offer additional areas to branch off wires and prevents wires from sliding or accidental removal from tubing.

Improves aesthics of assembled wire harness.

No tools required to disassemble.



Article Number

167-00219

Туре

CTHC-T767

Color Black (BK)

Quantity Per

carton



| Product Description         | Convoluted Loom fittings are single piece hinged connectors that<br>simply snap-on over slit and unslit loom tubing to secure wire<br>branchouts or, connect different tubing diameters. The unique wrap<br>around design makes installation easier and more efficient, while the<br>unique junction points make easy branchouts that keep wires from<br>sliding out of the tubing and eliminates need for secondary taping<br>operation. The polypropylene material creates a sleek assembly and<br>improves the appearance of the entire wiring assembly. |
|-----------------------------|---|
| Short Description           | Hinged Convoluted Tubing T-Fitting, L- 0.75" x C- 0.63" x R- 0.75", PP,<br>Black, 200/pkg   |
| Global Part Name            | CTHC-T767-PP-BK   |
|                             |   |
| Variant                     | Fittings  |
| Inner Diameter D (Imperial) | 0.75  |
| Inner Diameter D (Metric)   | 19.1  |
| Diameter D (Imperial)       | 0.75  |
| Diameter D (Metric)         | 19.1  |
|                             |   |
|                             |   |
| Material                    | Polypropylene (PP)  |
| Material Shortcut           | PP  |
| Flammability                | UL 94 HB  |
| Halogen Free                | Yes   |

| UV Resistant (Yes/No)        | No                              |
|------------------------------|---------------------------------|
| Use Conditions               | For Indoor Use Only             |
| Operating Temperature        | -4°F to +194°F (-20°C to +90°C) |
| Reach Compliant (Article 33) | No                              |
| ROHS Compliant               | Yes                             |
|                              |                                 |
| Package Quantity (Imperial)  | 200                             |
| Package Quantity (Metric)    | 200                             |
| Customs Number               | 3926909988                      |

© 2024 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Dis

Disclaimer

Terms and Conditions