


Specification Sheet

Part Number: 169-60023



Tubing protects cables and wires against automotive fluids, vibration wear

Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight



Convoluted Tubing, Unslit, 0.38" Dia, PA6, Black with Gray Stripe, 1500ft/carton

Article Number 169-60023

Type CTN380UNSLIT

Color Black with Gray Stripe (BKSTGY)

Quantity Per carton

Product Description HellermannTyton's Convoluted Tubing, also known at Split Loom

Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and

wires.

Short Description	Convoluted Tubing, Unslit, 0.38" Dia, PA6, Black with Gray Stripe, 1500ft/carton
Global Part Name	CTN380UNSLIT-PA6-BK
Length L (Imperial)	1500.0
Length L (Metric)	457.2
Variant	Unslit
Inner Diameter D (Imperial)	0.380
Inner Diameter D (Metric)	9.65
Diameter D (Imperial)	0.526
Diameter D (Metric)	13.36
Outside Diameter OD (Imperial)	0.526
Outside Diameter OD (Metric)	13.36
Nominal Diameter (Imperial)	0.38
Nominal Diameter (Metric)	9.65
Wall Thickness WT (Imperial)	0.005

0.127

Wall Thickness WT (Metric)

Material Polyamide 6 (PA6)

Material Shortcut PA6

Flammability UL 94 HB

UV Resistant (Yes/No) No

Use Conditions For Indoor Use Only

Operating Temperature -40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 1500

Package Quantity (Metric) 457.2

Customs Number 3926909988

© 2024 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions