

## Specification Sheet

Part Number: CTP20STD



Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture

Tubing protects cables and wires against automotive fluids, vibration wear

Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight

Convoluted Tubing, Slit, 2" Dia, PE, Black, 100 ft/carton

Article Number 169-60511

Type CTP20

Color Black (BK)

Quantity Per carton

**Product Description**

HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description	Convuluted Tubing, Slit, 2" Dia, PE, Black, 100 ft/carton
Global Part Name	CTP20-PE-BK
Length L (Imperial)	100.0
Length L (Metric)	30.4
Variant	Slit
Inner Diameter D (Imperial)	2.038
Inner Diameter D (Metric)	51.77
Diameter D (Imperial)	2.388
Diameter D (Metric)	60.66
Outside Diameter OD (Imperial)	2.388
Outside Diameter OD (Metric)	60.66
Nominal Diameter (Imperial)	2
Nominal Diameter (Metric)	50.8
Wall Thickness WT (Imperial)	0.011
Wall Thickness WT (Metric)	0.28

Material	Polyethylene (PE)
Material Shortcut	PE
Flammability	Not Flame Retardant
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	3926909988