HellermannTyton

Specification Sheet

Part Number: 169-60533

Millill . Million A

Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.

Tubing provides full coverage where spiral wrap or other coverings may not be suitable.

In harsh applications the tubing provides resistance to crushing, impact, and abrasion.

Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Convoluted Tubing, Slit, 0.75" Dia, PE, Red, 550 ft/carton

Article Number 169-60533 Туре **CTP340** Color Red (RD)

Quantity Per

carton

Product Description	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Short Description	Convoluted Tubing, Slit, 0.75" Dia, PE, Red, 550 ft/carton
Global Part Name	CTP340-PE-RD
Length L (Imperial)	550.0
Length L (Metric)	167.6
Inner Diameter D (Imperial)	0.759
Inner Diameter D (Metric)	19.28
Diameter D (Imperial)	0.989
Diameter D (Metric)	25.12
Outside Diameter OD (Imperial)	0.989
Outside Diameter OD (Metric)	25.12
Nominal Diameter (Imperial)	0.75
Nominal Diameter (Metric)	19.05

Wall Thickness WT (Imperial)	.005
Wall Thickness WT (Metric)	0.127
Material	Polyethylene (PE)
Material Shortcut	PE
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Use Conditions Operating Temperature	For Indoor Use Only -40°F to +199°F (-40°C to +93°C)
Operating Temperature	-40°F to +199°F (-40°C to +93°C)
Operating Temperature Reach Compliant (Article 33)	-40°F to +199°F (-40°C to +93°C) Yes
Operating Temperature Reach Compliant (Article 33)	-40°F to +199°F (-40°C to +93°C) Yes
Operating Temperature Reach Compliant (Article 33) ROHS Compliant	-40°F to +199°F (-40°C to +93°C) Yes Yes