

## **Specification Sheet**

Part Number: 169-60555

Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.

Tubing provides full coverage where spiral wrap or other coverings may not be suitable.

In harsh applications the tubing provides resistance to crushing, impact, and abrasion.

Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.



Convoluted Tubing, Slit, 1.25" Dia, PE, Orange, 250 ft/carton

Article Number 169-60555

Type CTP1140

Color Orange (OG), High Voltage (HV)

Quantity Per carton

| Product Description            | HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires. |
|--------------------------------|--|
| Short Description              | Convoluted Tubing, Slit, 1.25" Dia, PE, Orange, 250 ft/carton  |
| Global Part Name               | CTP1140-PE-OG  |
|                                |  |
| Length L (Imperial)            | 250.0  |
| Length L (Metric)              | 76.2   |
| Variant                        | Slit   |
| Inner Diameter D (Imperial)    | 1.257  |
| Inner Diameter D (Metric)      | 31.93  |
| Diameter D (Imperial)          | 1.50   |
| Diameter D (Metric)            | 38.10  |
| Outside Diameter OD (Imperial) | 1.50   |
| Outside Diameter OD (Metric)   | 38.10  |

1-1/4

Nominal Diameter (Imperial)

| Nominal Diameter (Metric)    | 31.75                            |
|------------------------------|----------------------------------|
| Wall Thickness WT (Imperial) | 0.006                            |
| Wall Thickness WT (Metric)   | 0.152                            |
|                              |                                  |
|                              |                                  |
| Material                     | Polyethylene (PE)                |
| Material Shortcut            | PE                               |
| Flammability                 | Not Flame Retardant              |
| Halogen Free                 | No                               |
| UV Resistant (Yes/No)        | No                               |
| Use Conditions               | For Indoor Use Only              |
| Operating Temperature        | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes                              |
| ROHS Compliant               | Yes                              |
|                              |                                  |
| Package Quantity (Imperial)  | 250                              |
| Package Quantity (Metric)    | 76.20                            |
| Customs Number               | 3926909988                       |

© 2024 HellermannTyton. All Rights Reserved. RoHS/WEEE Compliance Contact Us Disclaimer Terms and Conditions