HellermannTyton

Specification Sheet

Part Number: 170-03230



Self-wrapping feature allows easy installation and future access to wire and cables.

Unique blend and construction using monofilament and mutifilament strands provide flexibility, high coverage and abrasion resistance.

Extra overlapping design keeps wires contained even in tight bend conditions.

Braided Sleeving, Woven Convoluted Wrap, 3/8" Dia, PET, Orange, 150.0 ft/reel

Article Number	170-03230
Туре	BSPW380
Color	Orange (OG)
Quantity Per	reel
Product Description	Split Wrap Woven Sleeving is a self-closing sleeving manufactured from a unique blend of monofilament and multifilament polyester fibers that resemble a tightly woven material. The wrap around design provides increased flexibility, better coverage and greater resistance from abrasion for wires, cables and assemblies. Can also be used to reduce noise in applications that involve movement, while protecting sensitive electronics and communication systems from dust and debris.
Short Description	Braided Sleeving, Woven Convoluted Wrap, 3/8" Dia, PET, Orange, 150.0 ft/reel

Length L (Imperial)	150.0
Length L (Metric)	45.7
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.5
Bundle Diameter Max (Imperial)	0.38
Bundle Diameter Max (Metric)	9.53
Diameter D (Imperial)	0.375
Diameter D (Metric)	10.0
Nominal Diameter (Imperial)	0.394
Nominal Diameter (Metric)	10.0
Wall Thickness WT (Imperial)	0.027
Wall Thickness WT (Metric)	0.7

Material

Polyester (PET)

Flammability	FMVSS 302 UL 94 V-0
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-94°F to +302°F (-70°C to +150°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	150.0
Package Quantity (Metric)	45.7
Customs Number	5806322000

© 2024 HellermannTyton. All Rights Reserved.			
Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions