

## Specification Sheet

Part Number: 181-00599

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High-Density Slotted-Wall Wiring Duct, 1" x 2", Non-Adhesive, PVC, Black, 120 ft/carton

Article Number 181-00599

Type SLHD1X2

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

|                                  |   |
|----------------------------------|---|
| Short Description                | High-Density Slotted-Wall Wiring Duct, 1" x 2", Non-Adhesive, PVC, Black, 120 ft/carton |
| Global Part Name                 | SLHD1X2-PVC-BK  |
| Length L (Imperial)              | 6.0   |
| Length L (Metric)                | 1.83  |
| Fixation Method                  | Non-Adhesive  |
| Width W (Imperial)               | 1.0   |
| Width W (Metric)                 | 25.4  |
| Height H (Imperial)              | 2.07  |
| Height H (Metric)                | 52.6  |
| Mounting Hole Centers (Imperial) | 2.0   |
| Material                         | Polyvinylchloride (PVC)   |
| Material Shortcut                | PVC   |
| Halogen Free                     | No  |
| UV Resistant (Yes/No)            | No  |

|                              |  |
|------------------------------|--|
| Use Conditions               | For Indoor Use Only                              |
| Operating Temperature        | +122°F (+50°C)                                   |
| Reach Compliant (Article 33) | No   |
| ROHS Compliant               | Yes  |
| Certification/Specification  | CSA EN 50085-2-3_1A EN 50085-1:2005 + A1:2013 UL |
| UL Recognized (US)           | Yes  |
| Package Quantity (Imperial)  | 120.0  |
| Package Quantity (Metric)    | 36.58  |
| Customs Number               | 3925900000                                       |

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)