

Specification Sheet

Part Number: 181-05515

Solid wall construction provides excellent coverage to keep wires clean.

Durable material protects wires from damage, with long-lasting performance.

Available standard colors complement or contrast in light and dark environments.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



Solid-Wall Wiring Duct, .75" x .75", Non-Adhesive, PVC, Black, 30ft/box

Article Number 181-05515

Type SD,75X,75

Color Black (BK)

Quantity Per box

Product Description HellermannTyton Solid Wall Wiring Duct efficiently routes and protects wire. Solid wall wiring duct is designed for straight wire runs where breakouts are not required. Solid wall wiring duct is manufactured from high-impact, rigid PVC; comes in standard colors of white, gray and black; and is available in 6-foot lengths.

Short Description Solid-Wall Wiring Duct, .75" x .75", Non-Adhesive, PVC, Black, 30ft/box

Global Part Name	SD,75X,75-PVC-BK
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	0.75
Width W (Metric)	19.1
Height H (Imperial)	0.80
Height H (Metric)	20.3
Mounting Hole Centers (Imperial)	4.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	+122°F (+50°C)
Reach Compliant (Article 33)	No

ROHS Compliant Yes

Certification/Specification UL EN 50085-2-3_1A CSA EN 50085-1:2005 + A1:2013

UL Recognized (US) Yes

Package Quantity (Imperial) 30

Package Quantity (Metric) 9.14