

Specification Sheet

Part Number: 181-44014

A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.

Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.

Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)



Solid Wall Wiring Duct, With Cover, 4" X 4", PVC, White, 120ft/Carton

Article Number 181-44014

Type SD4X4W/TC4

Color White (WH)

Quantity Per carton

Product Description HellermannTyton Solid Wall Wiring Duct efficiently routes and protects

wire. Solid wall wiring duct is designed for straight wire runs where breakouts are not required. Solid wall wiring duct is manufactured from high-impact, rigid PVC; comes in standard colors of white, gray and

black; and is available in 6-foot lengths.

Short Description Solid Wall Wiring Duct, With Cover, 4" X 4", PVC, White, 120ft/Carton

| Globa | l Dort | NIOMO |
|--------|--------|-------|
| UNIODA | ı Pan | Name |

SD4X4W/TC4-PVC-WH

Length L (Imperial)

6.0

Length L (Metric)

1.83

Width W (Imperial)

4.0

Width W (Metric)

101.6

Height H (Imperial)

4.07

Height H (Metric)

103.40

Mounting Hole Centers (Imperial)

4.0

Material

Polyvinylchloride (PVC)

Material Shortcut

PVC

Halogen Free

No

UV Resistant (Yes/No)

No

Use Conditions

For Indoor Use Only

Operating Temperature

+122°F (+50°C)

Reach Compliant (Article 33)

No

| ROHS Compliant | Yes |
|-----------------------------|--|
| Certification/Specification | EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A UL CSA |
| UL Recognized (US) | Yes |
| | |
| Package Quantity (Imperial) | 120 |
| Package Quantity (Metric) | 36.58 |

 $\hbox{@\,}2024$ HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions