

Specification Sheet

Part Number: 184-22208

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High Density Slotted Wall Wiring Duct, 1" x 1", Non-Adhesive, PVC, Gray, 7FT, 140ft/Carton

Article Number 184-22208

Type SLHD1X1

Color Gray (GY)

Quantity Per carton

Product Description HellermannTyton High-Density Slotted Wall Wiring Duct features narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

| | |
|----------------------------------|--|
| Short Description | High Density Slotted Wall Wiring Duct, 1" x 1", Non-Adhesive, PVC, Gray, 7FT, 140ft/Carton |
| Global Part Name | SLHD1X1-PVC-GY |
| Length L (Imperial) | 7 |
| Length L (Metric) | 2.13 |
| Width W (Imperial) | 1.00 |
| Width W (Metric) | 25.40 |
| Height H (Imperial) | 1.06 |
| Height H (Metric) | 26.92 |
| Mounting Hole Centers (Imperial) | 2.00 |
| Material | Polyvinylchloride - rigid extrusion grade (PVC) |
| Material Shortcut | PVC |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor Use Only |
| Operating Temperature | +122°F (+50°C) |

| | |
|------------------------------|--|
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| Certification/Specification | EN 50085-1:2005 + A1:2013 CSA UL EN 50085-2-3_1A |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 140.0 |
| Package Quantity (Metric) | 42.67 |
| Customs Number | 3925900000 |

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)