## HellermannTyton

## **Specification Sheet**

Part Number: SNP1.5GHS0M4

Installation and removal can be five times faster

than conventional clamps

Heat stabilized material is suitable for high temperature applications.

Completely reusable

.

.

.

Will not rust or corrode

Safety engineered.

No protruding band or cluster.

Can be installed with hose in place



One-hand installation for tight places.

Snapper Hose Clamp, 0.32 - 0.35" Bundle Diameter, PA66GF13, Black, 1000/pkg

Article Number

190-00035

**SNP1.5** 

| Color                          | Black (BK)  |
|--------------------------------|---|
| Quantity Per                   | bag   |
| Product Description            | The Snapper Hose Clamp features a ratchet-style closure for reduced<br>assembly time. It can be added after connection of the hose. Release<br>by sliding the ratchet ends apart. Snappers can be used in under-hood<br>applications and are stable in a wide variety of chemicals including<br>salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils and<br>greases. They are manufactured in black PA66 glass filled, impact<br>modified, heat stabilized material. Custom design and color options are<br>available based upon application and volume requirements. |
| Short Description              | Snapper Hose Clamp, 0.32 - 0.35" Bundle Diameter, PA66GF13, Black, 1000/pkg   |
| Global Part Name               | SNP1.5-PA66GF13-BK  |
|                                |   |
| Fixation Method                | Plug-in mounting  |
| Variant                        | Closed  |
| Bundle Diameter Min (Imperial) | 0.31  |
| Bundle Diameter Min (Metric)   | 8.0   |
| Bundle Diameter Max (Imperial) | 0.35  |
| Bundle Diameter Max (Metric)   | 8.9   |
| Wall Thickness WT (Imperial)   | .055  |
| Wall Thickness WT (Metric)     | 1.414   |

| Material                     | Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%) |
|------------------------------|--|
| Material Shortcut            | PA66GF13   |
| Flammability                 | UL 94 HB   |
| UV Resistant (Yes/No)        | No   |
| Use Conditions               | For Indoor and Outdoor Use   |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C)                                      |
| Reach Compliant (Article 33) | No   |
| ROHS Compliant               | Yes  |
|                              |  |
| Package Quantity (Imperial)  | 1000   |
| Package Quantity (Metric)    | 1000   |
| Customs Number               | 3926909988   |

© 2024 HellermannTyton. All Rights Reserved.