HellermannTyton

Specification Sheet

Part Number: SNP10GHS0C2

Installation and removal can be five times faster

than conventional clamps.

Heat stabilized material is suitable for high temperature applications.

Completely reusable.

Will not rust or corrode.

Safety engineered.

No protruding band or cluster.

Can be installed with hose in place.

One-hand installation for tight places.

Snapper Hose Clamp, 0.57" - 0.65" Bundle Diameter, PA66GF13, Black, 100/pkg

Article Number

192-10100

Type

SNP10

Color

Black (BK)

Quantity Per



bag

Product Description	The Snapper Hose Clamp features a ratchet-style closure for reduced assembly time. It can be added after connection of the hose. Release by sliding the ratchet ends apart. Snappers can be used in under-hood applications and are stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils and greases. They are manufactured in black PA66 glass filled, impact modified, heat stabilized material. Custom design and color options are available based upon application and volume requirements.
Short Description	Snapper Hose Clamp, 0.57" - 0.65" Bundle Diameter, PA66GF13, Black, 100/pkg
Global Part Name	SNP10-PA66HIRHSGF15-BK
Fixation Method	Plug-in mounting
Variant	Closed
Bundle Diameter Min (Imperial)	0.57
Bundle Diameter Min (Metric)	14.5
Bundle Diameter Max (Imperial)	0.65
Bundle Diameter Max (Metric)	16.6
Nominal Diameter (Imperial)	0.63
Nominal Diameter (Metric)	16
Wall Thickness WT (Imperial)	.069
Wall Thickness WT (Metric)	1.8

Polyamide 6.6, impact modified, heat stabilized, glass-fiber reinforced (PA66HIRHSGF15)
PA66HIRHSGF15
UL 94 HB
No
For Indoor and Outdoor Use
-40°F to +257°F (-40°C to +125°C)
Yes
Yes
100
100
3926909988

© 2024 HellermannTyton. All Rights Reserved.