

Specification Sheet

Part Number: 211-60008



P-Clamps easily guide and locate wire and cables up to 1" in diameter.

Designed with a radius edge to prevent chafing and cutting into insulation.

P-Clamp, 0.39" Wide, 0.63" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66HS Black, 100/pkg

Article Number 211-60008

Type H9P

Color Black (BK)

Quantity Per pcs.

Product Description HellermannTyton P-Clamps easily guide and locate wires and cables. The clamps are designed with a radius edges to prevent chafing and cutting into insulation. Available sizes up to 1" bundle diameters.

Short Description P-Clamp, 0.39" Wide, 0.63" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66HS Black, 100/pkg

Global Part Name H9P-PA66HS-BK

| | |
|---------------------------------------|--|
| Fixation Method | screw-hole |
| Variant | Closed |
| Width W (Imperial) | 0.39 |
| Width W (Metric) | 10.0 |
| Bundle Diameter Max (Imperial) | 0.63 |
| Bundle Diameter Max (Metric) | 16.0 |
| Nominal Diameter (Imperial) | 0.63 |
| Nominal Diameter (Metric) | 16.0 |
| Wall Thickness WT (Imperial) | 0.059 |
| Wall Thickness WT (Metric) | 1.5 |
| Mounting Hole Diameter D (Imperial) | 0.17 |
| Mounting Hole Diameter D (Metric) | 4.2 mm |
| Mounting Hole Diameter D Max (Metric) | 4.2 |
| Mounting Hole Centers (Imperial) | 0.63 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |

| | |
|------------------------------|-----------------------------------|
| Material Shortcut | PA66HS |
| Flammability | UL 94 V-2 |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |