

Specification Sheet

Part Number: 411-05018



Used in conjunction with a circular grooved adaptor for strain relief

Heat Shrink Molded Shapes, 1100 Series 90-Degree with Rib - MIL, 1105-4-G, PO-X, BK, 1/bag

|                     |                                                                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 411-05018                                                                                                                                          |
| Type                | 1105-4-G                                                                                                                                           |
| Color               | Black (BK)                                                                                                                                         |
| Quantity Per        | bag                                                                                                                                                |
| Product Description | Helashrink 1100 series, with rib - MIL style, provides strain relief for harness systems when used in conjunction with a circular grooved adaptor. |
| Short Description   | Heat Shrink Molded Shapes, 1100 Series 90-Degree with Rib - MIL, 1105-4-G, PO-X, BK, 1/bag                                                         |
| Global Part Name    | 1105-4-G-PO-X-BK                                                                                                                                   |

|                             |                                    |
|-----------------------------|------------------------------------|
| Variant                     | For plug                           |
| Material                    | Polyolefin, cross-linked (PO-X)    |
| Material Shortcut           | PO-X                               |
| Flammability                | ASTM D635                          |
| UV Resistant (Yes/No)       | No                                 |
| Use Conditions              | For Indoor Use Only                |
| Operating Temperature       | -103°F to +302°F (-75°C to +150°C) |
| ROHS Compliant              | Yes                                |
| Package Quantity (Imperial) | 1                                  |
| Package Quantity (Metric)   | 1                                  |