

Specification Sheet

Part Number: 415-06018



Provides strain relief and mechanical protection for Min-D series connectors.

Heat Shrink Molded Shapes, 1500 Series D-Boot Straight, 1506-3-G, PO-X, BK, 1/bag

|                     |                                                                                                                                                       |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 415-06018                                                                                                                                             |
| Type                | 1506-3-G                                                                                                                                              |
| Color               | Black (BK)                                                                                                                                            |
| Quantity Per        | bag                                                                                                                                                   |
| Product Description | Helashrink 1500 series, with top entry, has a unique design that allows perfect orientation on installation and can be supplied with or without lips. |
| Short Description   | Heat Shrink Molded Shapes, 1500 Series D-Boot Straight, 1506-3-G, PO-X, BK, 1/bag                                                                     |
| Global Part Name    | 1506-3-G-PO-X-BK                                                                                                                                      |

|                             |                                    |
|-----------------------------|------------------------------------|
| Material                    | Polyolefin, cross-linked (PO-X)    |
| Material Shortcut           | PO-X                               |
| Flammability                | ASTM D635                          |
| UV Resistant (Yes/No)       | No                                 |
| Use Conditions              | For Indoor Use Only                |
| Operating Temperature       | -103°F to +302°F (-75°C to +150°C) |
| ROHS Compliant              | Yes                                |
| Package Quantity (Imperial) | 1                                  |
| Package Quantity (Metric)   | 1                                  |