

Specification Sheet

Part Number: 556-05000

300 dpi print head for high-resolution printing.

Ethernet ready for easy network connectivity.

Print speeds up to 7.87 inches/second for fast label production.

Floating print head to automatically adjust to varying media thickness such as printable heat shrink tubing.



TrakMark DS Thermal Transfer Printer, Double Sided, 300 DPI, Gray, 1/pkg

Article Number 556-05000

Type TrakMark DS

Color Gray (GY)

Quantity Per EA

Product Description HellermannTyton's wireless-ready TrakMark DS thermal transfer printer is designed for medium- to high-volume users of double-sided ShrinkTrak. This printer prints on both sides of the media, supported by HellermannTyton's TagPrint® Pro label printing software. The TrakMark's user-friendly design features an LCD touch screen for simple navigation. The optional cutter can cut through the thickest identification material. The TrakMark DS is designed to handle all sizes of HellermannTyton's ShrinkTrak markers.

Short Description	TrakMark DS Thermal Transfer Printer, Double Sided, 300 DPI, Gray, 1/pkg
Global Part Name	TrakMark DS-PL-GY
Length L (Imperial)	21.0
Length L (Metric)	533.4
Width W (Imperial)	9.0
Width W (Metric)	248
Height H (Imperial)	15.0
Height H (Metric)	395
Depth D (Imperial)	21.0
Depth D (Metric)	554
Material	Plastic (PL)
Material Shortcut	PL
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only

Operating Temperature	+40°F to +104°F (+4°C to +40°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL ANSI/UL 60950-21 UL ANSI/UL 60950-22 iLab EN 55022:2011-12 iLab EN 61000-6-2 UL ANSI/UL 60950-23 iLab EN 61000-3-3 CE 2004/108/EG CE 2014/35/EU FCC UL ANSI/UL 60950-1 iLab EN 61000-3-2 iLab EN 55024:2011-09
UL Listed (US)	Yes
Package Quantity (Imperial)	1
Package Quantity (Metric)	1
Customs Number	8443321050

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)