

## Specification Sheet

Part Number: 596-00379

Pre-Printed Signal Word labels come with the header pre-printed in colors so that only one color of ribbon is needed to complete the message panel.

Labels are pre-made to the most recent ANSI standards so that code compliance is assured.



Pre-Printed Signal Panel labels can be printed using standard thermal transfer printers to reduce labor, eliminate minimum orders and allow the user to create labels on demand when needed.

Pre-Printed Header Label, DANGER, Blank Yellow Triangle, 1.35" x 2.75", PET, Red, 250/roll

Article Number 596-00379

Type DV275X135

Color Red (RD)

Quantity Per reel

Product Description These labels come with preprinted color headers so only one color of ribbon is needed to complete the message panel. Labels can be used with TagPrint® Pro label software and HellermannTyton thermal transfer printers to reduce labor, eliminate minimum orders and allow the user to create labels on demand.

Short Description Pre-Printed Header Label, DANGER, Blank Yellow Triangle, 1.35" x 2.75", PET, Red, 250/roll

|                           |  |
|---------------------------|--|
| Global Part Name          | DV275X135-336/926-RD   |
| Width W (Imperial)        | 2.75   |
| Width W (Metric)          | 69.85  |
| Thickness T (Metric)      | 64.0   |
| Height H (Imperial)       | 1.35   |
| Height H (Metric)         | 34.29  |
| Width of Liner (Metric)   | 35.56  |
| Width of Liner (Imperial) | 1.40   |
| Material                  | Type 336/926, Polyester, UV stabilized, clear polyester laminate (336/926) |
| Material Shortcut         | 336/926  |
| Adhesive                  | Acrylic  |
| Halogen Free              | No   |
| UV Resistant (Yes/No)     | Yes  |
| Use Conditions            | For Indoor and Outdoor Use   |

|                                |                                   |
|--------------------------------|-----------------------------------|
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature          | -40°F to +302°F (-40°C to +150°C) |
| Reach Compliant (Article 33)   | Yes                               |
| ROHS Compliant                 | Yes                               |
| Certification/Specification    | NEC2020 NEC2014 NEC2017 NEC2011   |
| UL Recognized (US)             | Yes                               |
| Package Quantity (Imperial)    | 250                               |
| Package Quantity (Metric)      | 250                               |
| Customs Number                 | 3919102055                        |
| Labels per Column              | 1                                 |
| Labels per Row                 | 1                                 |