

## Specification Sheet

Part Number: 596-00892

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC® code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.



Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, Printable, PV AC DISCONNECT RATING, 3.75" x 1.0", PET, Red, 50/roll

Article Number 596-00892

Type PVACDIS17

Color Red (RD)

Quantity Per reel

**Product Description** Designed with cross-laminated UV stable materials, these variable print Solar Installation Labels are designed to accept printing from any standard thermal transfer printer using a resin-based ink ribbon for the best durability. Print your voltage information directly on the label and then laminate with an optional clear acrylic laminate material for added protection. These labels can be used to print disconnecting means and breaker series directly on the labels for a more professional result and a smoother inspection process.

|                        |  |
|------------------------|--|
| Short Description      | Solar Label, Printable, PV AC DISCONNECT RATING, 3.75" x 1.0", PET, Red, 50/roll |
| Global Part Name       | PVACDIS17-840/281-RD   |
| Width W (Imperial)     | 3.75   |
| Width W (Metric)       | 95.25  |
| Thickness T (Imperial) | 0.0025   |
| Thickness T (Metric)   | 64.0   |
| Height H (Imperial)    | 1.0  |
| Height H (Metric)      | 25.4   |
| Material               | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)       |
| Material Shortcut      | 840/281  |
| Adhesive               | Acrylic  |
| Halogen Free           | Yes  |
| UV Resistant (Yes/No)  | Yes  |
| Use Conditions         | For Indoor and Outdoor Use   |

|                                |   |
|--------------------------------|---|
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C)         |
| Operating Temperature          | -40°F to +302°F (-40°C to +150°C)         |
| Reach Compliant (Article 33)   | Yes                                       |
| ROHS Compliant                 | Yes                                       |
| Certification/Specification    | CSA 66956 IFC 2012 NEC2017 NEC2020 UL 969 |
| Warranty (US)                  | Yes                                       |
| UL Recognized (US)             | Yes                                       |
| Package Quantity (Imperial)    | 50  |
| Package Quantity (Metric)      | 50  |
| Customs Number                 | 3919102055                                |
| Labels per Column              | 1   |
| Labels per Row                 | 1   |