

## **Specification Sheet**

Part Number: 596-01003

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

RAPID SHUTDOWN FOR SOLAR PV SYSTEM

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, Reflective, RAPID SHUTDOWN FOR SOLAR PV SYSTEM, 6.5" X 1.0", VL, Red, 50/roll

Article Number 596-01003

Type RSSPVS

Color Red (RD)

Quantity Per reel

Product Description HellermannT

HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code® (NEC®) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder-coated surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, Reflective, RAPID SHUTDOWN FOR SOLAR PV SYSTEM, 6.5" X 1.0", VL, Red, 50/roll
Global Part Name	RSSPVS-505/281-RD
Width W (Imperial)	6.5
Width W (Metric)	165.1
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	1.0
Height H (Metric)	25.40
Width of Liner (Metric)	28.57
Width of Liner (Imperial)	1.125
Material	Type 505/281, UV stabilized, reflective vinyl with clear polyester laminate (505/281)
Material Shortcut	505/281
Adhesive	Acrylic

No

Halogen Free

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Operating Temperature -40°F to +174°F (-40°C to +79°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant Yes

Certification/Specification NEC2020 UL 969

UL Recognized (US) Yes

Package Quantity (Imperial) 50

Package Quantity (Metric) 50

Customs Number 3919102055

Labels per Column 1

Labels per Row 1