

Specification Sheet

Part Number: 904-02662

Offset enables installers to secure bundles away from obstructions, heat or sources of abrasion.

All-in-one bundling and fastening solution reduces costs and assembly time.

Versatile, high-performance fir tree design demonstrates easy insertion with high extraction resistance for a 6.1 - 7.0 mm hole.

Solar-rated PA66HIRHSUV material provides long-term outdoor performance.



1-Pc Cable Tie/Offset Fir Tree w/Disc, 25mm Offset/90°, 9.4"L, 6.1-7mm Hole, PA66HIRHSUV, Blk, 3000/ctn

Article Number	904-02662
Type	T50ROSFT6SO25R
Color	Black (BK)
Quantity Per	carton
Product Description	One-piece offset cable tie and mount offers a simple bundling and mounting solution on Series 7 panels. Offset feature positions bundles away from a mounting hole. The disc feature adds stability to reduce rocking and prevent rattling.
Short Description	1-Pc Cable Tie/Offset Fir Tree w/Disc, 25mm Offset/90°, 9.4"L, 6.1-7mm Hole, PA66HIRHSUV, Blk, 3000/ctn

Global Part Name

T50ROSFT6SO25R-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 222

Length L (Imperial) 9.4

Length L (Metric) 237.7

Offset Length (Imperial) 0.98

Offset Length (Metric) 25.0

Fixation Method Fir tree for round holes

Width W (Imperial) 0.20

Width W (Metric) 5.1

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.6

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Height H (Imperial) 0.97

Height H (Metric) 15.1

Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.32
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	8.25
Mounting Hole Diameter D (Imperial)	0.24 - 0.28
Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)

ROHS Compliant	Yes
Package Quantity (Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988