

## 22 AWG / Solid Bare Copper

Multiconductor - 300 Volt  
Polyethylene Insulation  
Unshielded - 60°C



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Solid bare copper conductors

### Category Insulation Description:

- Polyethylene (PE)

### Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC) over cabled conductors

### Applications:

- Applications include computers, communications, instrumentation, sound, control, audio, and data transmission
- Designed to protect signal integrity under critical conditions by reducing hum, noise, and crosstalk

### Standards:

- NEC CM
- UL Style: 2092, 2093, 2094

Color Code Chart	
# of Conductors	Color
1	Red
2	Green
3	Yellow
4	Black

Part Number Table

Part#	Houston Wire & Cable	Gauge	Conductors	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D92202-SO		22	2	0.018	0.022	0.167	19
D92203-SO	22-03CMR	22	3	0.018	0.022	0.176	23
D92204-SO	22-04CMR	22	4	0.018	0.025	0.199	27

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)  
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto  
© 2020 Omni Cable LLC