

600V MC CABLE (THHN/THWN-2 Insulation) Solid

Category Conductor Description:

- Plain annealed copper, Concentric-stranded, Class B (ASTM B8), Solid round wire (ASTM B 258)

Filler:

- Non-hygroscopic

Category Jacket Description:

- Nylon

Category Insulation Description:

- THHN/THWN-2 PVC (polyvinyl chloride) with color-coded nylon (polyamide) covering

Aarmor:

- Aluminium tape, Interlock

Standards:

- UL 1569: E38918 UL 83: E15119 ASTM B3 FT4/IEEE 1202 NFPA 70 (National Electrical Code), Article 330 Federal Specification A-A59562

Part Number Table

| Part# | Gauge | Outside Diameter Inches | Insulation Thickness |
|---------------|--------------|--------------------------------|-----------------------------|
| MC21202-250CL | 12 | 0.475 | 0.014 |
| MC21202 | 12 | 0.475 | 0.014 |
| MC21402 | 14 | 0.43 | 0.014 |
| MC21402-250CL | 14 | 0.43 | 0.014 |
| MC21403-250CL | 14 | 0.465 | 0.014 |
| MC21404 | 14 | 0.495 | 0.014 |
| MC21404-250CL | 14 | 0.495 | 0.014 |
| MC21403 | 14 | 0.465 | 0.014 |
| MC21203-250CL | 12 | 0.502 | 0.014 |
| MC21203 | 12 | 0.502 | 0.014 |
| MC21002-250CL | 10 | 0.535 | 0.02 |
| MC21204 | 12 | 0.539 | 0.02 |
| MC21204-250CL | 12 | 0.539 | 0.014 |
| MC21002 | 10 | 0.535 | 0.02 |
| MC21003 | 10 | 0.58 | 0.02 |
| MC21003-250CL | 10 | 0.58 | 0.02 |
| MC21004 | 10 | 0.623 | 0.02 |
| MC21004-250CL | 10 | 0.623 | 0.02 |

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC