


## 600V Teck 90, Multi-conductor w/ Ground

Aluminum Interlocked Armor  
Teck 90  
Control  
90°C - 600 Volt



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Bare copper Class B stranding compressed concentric round to ASTM B26

### Spec Ground:

- The ground consists on one uninsulated stranded bare copper conductor

### Armor:

- Aluminum interlocked armor

### Applications:

- Suitable for use in ventilated, non-ventilated and ladder cable trays, direct earth burial or raceways, and for exposed or concealed wiring in wet, damp or dry locations
- Suitable for use in wet or dry locations when installed in accordance with the NEC

### Category Insulation Description:

- Cross-linked Polyethylene (XLPE) Type RW90

### Inner Jacket:

- Black, lead-free, flame retardant, moisture and sunlight resistant Polyvinyl Chloride (PVC)

### Outer Jacket:

- Black, lead-free, flame retardant, moisture and sunlight resistant Polyvinyl Chloride (PVC)

### Standards:

- UL 1581
- IEEE 1202
- Hazardous location rating - HL
- OSHA Acceptable
- CSA FT 1 & FT 4
- CSA Standard C22.2 No. 131 and No. 174

**Part Number Table**

<b>Part#</b>	<b>Houston Wire &amp; Cable</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Ground Gauge</b>	<b>Insulation Thickness</b>	<b>Nominal OD over Armor</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>	<b>Material Weight (KG/KM)</b>
T31402	HW330.pdf	14	2	14	0.03	.580	0.67	190	282
T31403	HW330.pdf	14	3	14	0.03	.600	0.69	218	324
T31404	HW330.pdf	14	4	14	0.03	.640	0.72	246	366
T31405	HW330.pdf	14	5	14	0.03	.680	0.76	276	410
T31407	HW330.pdf	14	7	14	0.03	.740	0.82	329	489
T31410		14	10	14	0.03	.880	0.96	450	669
T31412	HW330.pdf	14	12	14	0.03	.900	0.99	492	732
T31415		14	15	14	0.03	.960	1.04	550	818
T31420	HW330.pdf	14	20	14	0.03	1.13	1.21	745	1108
T31425		14	25	14	0.03	1.22	1.3	919	1367
T31202		12	2	14	0.03	.620	0.7	221	328
T31203	HW330.pdf	12	3	14	0.03	.650	0.73	259	385
T31204	HW330.pdf	12	4	14	0.03	.690	0.77	290	431
T31205	HW330.pdf	12	5	14	0.03	.730	0.81	412	613
T31207		12	7	14	0.03	.830	0.91	439	653
T31212	HW330.pdf	12	12	14	0.03	1.01	1.1	643	956
T31002	HW330.pdf	10	2	12	0.03	.670	0.75	276	410
T31003	HW330.pdf	10	3	12	0.03	.700	0.78	317	471
T31004	HW330.pdf	10	4	12	0.03	.740	0.83	382	568
T31006		10	6	12	0.03	.880	0.96	515	766
T31008		10	8	12	0.03	.930	1.02	637	947
T31012		10	12	12	0.03	1.150	1.23	901	1340

Note: The information in this specification sheet is approximate and subject to standard industry and manufacturer tolerances. Please verify specific requirements with your Omni Cable account manager.

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •**  
**St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**