

# Armored Cable

## 600V - UL Type MC - 14 & 12 AWG

Aluminum Interlocked Armor  
XLPE Insulation - PVC Jacket  
90°C - 600 Volt  
14 AWG & 12 AWG - Multi-conductor



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Bare compressed copper Class B stranding per ASTM B3 and B8

### Armor:

- Aluminum interlocked armor

### Applications:

- In all raceways or direct burial In wet or dry locations
- Permitted for use in Class I, Division II and Class II, Division II, and Class III, Division I and II per NEC Article 334

### Category Insulation Description:

- Flame-retardant Cross-linked Polyethylene (XLPE)

### Category Jacket Description:

- Flame-retardant, moisture and sunlight resistant Polyvinyl Chloride (PVC)

### Standards:

- UL 1569, UL 44, UL 1581, UL
- Type MC-600 volts
- NEC Type XHHW-2 conductors
- IEEE 1202
- OSHA Acceptable

**Part Number Table**

<b>Part#</b>	<b>Houston Wire &amp; Cable</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Ground Gauge</b>	<b>Insulation Thickness</b>	<b>Nominal OD over Armor</b>	<b>Nominal OD Overall</b>	<b>Material Weight (Lbs./M')</b>
Y11207A		12	7	12	0.03	0.72	0.69	246
Y11403A	HW300.pdf	14	3	14	0.03	0.52	0.63	183
Y11404A	HW300.pdf	14	4	14	0.03	0.55	0.66	233
Y11405A	HW300.pdf	14	5	14	0.03	0.59	0.69	246
Y11407A	HW300.pdf	14	7	14	0.03	0.64	0.74	297
Y11409A	HW300.pdf	14	9	14	0.03	0.7	0.83	379
Y11412A	HW300.pdf	14	12	14	0.03	0.8	0.9	460
Y11419A	HW300.pdf	14	19	14	0.03	0.99	1.02	621
Y11202A	HW300.pdf	12	2	12	0.03	0.53	0.64	218
Y11205A	HW300.pdf	12	5	12	0.03	0.65	0.76	325
Y11212A	HW300.pdf	12	12	12	0.03	0.86	0.89	596
Y11219A	HW300 01219	12	19	12	0.03	0.99	1.1	830

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC