

600V - UL Type MC - 4 Conductor

Aluminum Interlocked Armor
90°C - 600 Volt
UL Type MC
4-Conductor



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Bare compressed copper Class B stranding per ASTM B3 and B8

Category Assembly Description:

- Conductors are cabled with suitable fillers and bare copper ground conductor Cable core is covered with binder tape

Armor:

- Aluminum interlocked armor

Applications:

- In all raceways or direct burial In wet or dry locations
- Permitted for use in Class I, Division II and Class II, Division II, and Class III, Division I and II per NEC Article 334

Category Insulation Description:

- Flame-retardant Cross-linked Polyethylene (XLPE)

Spec Ground:

- Annealed bare copper Class B stranding per ASTM B13

Category Jacket Description:

- Flame and sunlight resistant black PVC jacket

Standards:

- UL 1569, UL 44, UL 1581, UL Type MC-600 volts
- NEC Type XHHW-2 conductors
- IEEE 1202
- OSHA Acceptable

Part Number Table

Part#	Houston Wire & Cable	Gauge	Conductors	Ground Gauge	Insulation Thickness	Jacket Thickness	Nominal OD over Armor	Nominal OD Overall	Material Weight (Lbs./M')
Y11204A	HW300.pdf	12	4	12	0.03	0.05	0.58	0.71	272
Y11004A	HW300.pdf	10	4	10	0.03	0.05	0.68	0.77	355
Y10804A	HW301.pdf	8	4	10	0.045	0.05	0.81	0.9	494
Y10604A	HW301.pdf	6	4	8	0.045	0.05	0.91	1.01	655
Y10404A	HW301 00404	4	4	8	0.045	0.05	1.01	1.13	891
Y10204A	HW301 00204	2	4	6	0.045	0.05	1.15	1.28	1283
Y10104A	HW301 00104	1	4	6	0.055	0.05	1.37	1.41	1584
Y11/004A	HW301 10104	1/0	4	6	0.055	0.05	1.47	1.5	1900
Y12/004A	HW301 20104	2/0	4	6	0.055	0.06	1.57	1.61	2356
Y13/004A	HW301 30104	3/0	4	4	0.055	0.06	1.69	1.78	2916
Y14/004A	HW301 40104	4/0	4	4	0.055	0.06	1.83	1.9	3596
Y125004A	HW301 25004	250	4	4	0.065	0.06	1.99	2.07	4184
Y135004A	HW301 35004	350	4	3	0.065	0.075	2.25	2.32	5628
Y150004A	HW24A.pdf	500	4	2	0.065	0.075	2.57	2.66	7832
Y175004A		750	4	1	0.08	0.085	3.09	3.26	11825

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC