

Station Wire

Station Wire
CMX
300 Volts

Category Conductor Description:

- Solid bare copper

Pair Assembly:

- 2 conductors twisted to a left hand lay to form a pair

Category Jacket Description:

- Beige, Polyvinyl Chloride (PVC)

Standards:

- UL 444, Communications Cables
- UL 1581 Vertical Tray Flame Test
- NEC Article 800
- UL C(UL) Listed Type CMX
- California State Fire Marshal Approve
- Operating temperature -30°C to +75°C
- Meets Cat 3 Electrical properties

Category Insulation Description:

- Thermoplastic

Cable Core:

- 2 twisted pairs pulled in parallel and jacketed

Applications:

- Residential grade station wire, indoor/outdoor use
- UL Approved

Color Code Chart

# of Pairs	Color
1	Red & Green
2	Yellow & Black

Part Number Table

Part#	Gauge	Pairs	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
J52402	24	2	0.021	0.144	13
J52202	22	2	0.021	0.164	15.7

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC