


## #1/3, #6G, #18/9 TCERJP Generator Installation Tray Cable, 600V Aluminum & Copper Conductors, PVC Insulation and Jacket

### TCERJP1724AL9

### NEC 2023 Compliant

Rated 17-24kW for Propane and 17-26kW for Natural Gas



\*Product images are for illustrative purposes only and may differ from the actual product.

#### Category Conductor Description:

- 4 Parts: 1 AWG Class B stranded 8000 series aluminum 3C, 18 AWG Class K stranded bare copper 9C, 6 AWG Class B stranded 8000 series aluminum ground wire, Sunlight Resistant

#### Category Insulation Description:

- Polyvinyl Chloride (PVC) insulation

#### Category Jacket Description:

- Moisture resistant, polyvinyl chloride (PVC) insulation

#### Applications:

- Suited for use in cable trays, aerial or direct burial installations.
- Type TC-ER Power Control Generator Tray Cable
- JP rated for installation in accordance with Part II of Article 336

#### Standards:

- ASTM B3
- ASTM B174
- ASTM B801
- ICEA S-95-658 (NEMA WC 70)
- ICEA S-73-532 (NEMA WC 57)
- UL 83 Type THWN
- UL 1277
- UL THWN 600V
- UL Type TC-ER-JP 600V

Part Number Table

| Part#         | Outside Diameter Inches | Ground Gauge | Temperature   |
|---------------|-------------------------|--------------|---------------|
| TCERJP1724AL9 | 1.13                    | 6            | TCERJP1724AL9 |

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)  
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto  
© 2020 Omni Cable LLC