

## Bus Drop Cable

Bus Drop Cable  
60°C - 600 Volt - UL



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Bare Stranded copper

### Filler:

- Suitable fillers are used to make the cable round

### Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

### Standards:

- NEC 364-8, as branch wiring from busways
- UL Listed
- Rated for UV/Sunlight Resistant applications

### Category Insulation Description:

- Color coded Polyvinyl Chloride (PVC)

### Ground Wires:

- Stranded, placed in spaces between individual conductors

### Applications:

- Connection of stationary equipment
- PVC Jacket offers excellent resistance to grease, lubricants, oils and other fluids which are Used with various types of machinery

Color Code Chart	
# of Conductors	Color
1	Red
2	Black
3	White
4	Blue

**Part Number Table**

<b>Part#</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Ground No x AWG</b>	<b>Insulation Thickness</b>	<b>Jacket Thickness</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>
A81403	14	3	3 X 18	0.03	0.045	0.379	111
A81404	14	4	3 X 18	0.03	0.045	0.425	140
A81203	12	3	3 X 16	0.03	0.045	0.42	150
A81204	12	4	3 X 16	0.03	0.045	0.462	159
A81003	10	3	3 X 14	0.03	0.045	0.47	224
A81004	10	4	3 X 14	0.03	0.045	0.5	238
A80803	8	3	3 X 14	0.045	0.06	0.63	334
A80804	8	4	3 X 14	0.045	0.06	0.698	379
A80603	6	3	3 X 14	0.06	0.06	0.794	483
A80604	6	4	3 X 14	0.06	0.06	0.855	571
A80403	4	3	3 X 12	0.06	0.08	0.939	721
A80404	4	4	3 X 12	0.06	0.06	0.99	841
A80203	2	3	3 X 12	0.06	0.08	1.071	1034
A80204	2	4	3 X 12	0.06	0.06	1.28	1130

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •

St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC