

## Cathodic Protection Cable

Stranded Bare Copper  
Soft Drawn  
600 Volt - 75°C



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Soft annealed stranded copper per ASTM B-8

### Applications:

- Suitable for direct burial for use in cathodic protection systems for pipelines, storage tanks, pilings, well casings, cables, water storage tanks and other buried or water-submerged metallic structures

### Category Insulation Description:

- Black, High Molecular Weight Polyethylene (HMW-PE) per ASTM D-1248 I

### Standards:

- ICEA S-61-402
- NEMA WC-5
- Suitable for direct burial
- Chemical, oil, and moisture resistant
- Crush and abrasion resistant
- Sunlight resistant
- UL Listed as cathodic protection cable available upon request

**Part Number Table**

<b>Part#</b>	<b>Gauge</b>	<b>Stranding</b>	<b>Insulation Thickness</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>
M31401CP	14	7	0.11	0.29	38
M31201CP	12	7	0.11	0.309	48
M31201CP-04	12	7	0.11	0.309	48
M31001CP	10	7	0.11	0.316	60
M31001CP-04	10	7	0.11	0.316	60
M30801CP	8	7	0.11	0.368	88
M30801CP-04	8	7	0.11	0.368	88
M30601CP	6	7	0.11	0.498	124
M30601CP-04	6	7	0.11	0.498	124
M30401CP	4	7	0.11	0.445	182
M30401CP-04	4	7	0.11	0.445	182
M30201CP	2	7	0.11	0.51	262
M30201CP-04	2	7	0.11	0.51	262
M30101CP	1	19	0.125	0.584	344
M31/001CP	1/0	19	0.125	0.62	413
M31/001CP-04	1/0	19	0.125	0.62	413
M32/001CP	2/0	19	0.125	0.66	508
M32/001CP-04	2/0	19	0.125	0.66	508
M34/001CP	4/0	19	0.125	0.77	772
M34/001CP-04	4/0	19	0.125	0.77	772

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •**  
**St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**