

Direct Burial Filled

Direct Burial Filled

Category Conductor Description:

- Solid annealed Bare copper

Cable Core:

- Insulated Conductors are twisted into pairs with varying lays to minimize crosstalk and meet strict capacitance unbalance limits

Inner Jacket:

- Black, low density, high molecular weight Polyethylene inner Jacket is Extruded over the cable core assembly

Applications:

- This is a double jacketed, completely filled design. It is offered under REA Spec-54 with a choice of metal shielding tapes

Category Insulation Description:

- Solid, high-density polyolefin with Standard telephone industry REA Color-coding

Shield:

- Standard- .008" thick coated aluminum tape

Outer Jacket:

- Black, low density, high molecular weight Polyethylene compounded to withstand Sunlight temperature variations, and other environmental conditions

Part Number Table

Part#	Gauge	Insulation Thickness	Inner Jacket Thickness	Outer Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
J102202	22	.015"	.025"	.030"	.330"	51
J102203	22	.015"	.025"	.030"	.350"	62

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC