

## Festoon Cable

Festoon Cable  
105°C to -40°C  
PVC Jacket  
600 Volts



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Soft-drawn uncoated copper

### Category Insulation Description:

- Color-coded, flame- and oil-resistant PVC

### Category Jacket Description:

- Yellow flame- and oil-resistant PVC

### Applications:

- Primarily designed for use with festoon systems for the conveyance of electrical power and control to cranes, hoists, or any other equipment which travels with a lateral traversing motion
- Suitable for indoor or outdoor applications

### Standards:

- ASTM B-3
- ASTM B-172
- UL-62
- CSA 1447
- CSA FT-1
- UL VW-1

Color Code Chart	
# of Conductors	Color
1	Black
2	Red
3	Blue
4	Orange
5	Yellow
6	Brown

7	Red/Black Stripe
8	Light Blue/Black Stripe
9	Orange/Black Stripe
10	Yellow/Black Stripe
11	Brown/Black Stripe
12	Black/Red Stripe

**Part Number Table**

<b>Part#</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Stranding</b>	<b>Insulation Thickness</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>
FC11604	16	4	26/30	0.03	.1920 X .5580	135
FC11608	16	8	65/34	0.03	.2000 X 1.1100	194
FC11612	16	12	26/30	0.03	.2000 X 1.6050	292
FC11404	14	4	41/30	0.03	.2400 X .6900	138
FC11408	14	8	41/30	0.03	.2400 X 1.3340	254
FC11412	14	12	41/30	0.03	.2400 X 1.9500	380
FC11204	12	4	65/30	0.03	.2300 X .7100	180
FC11208	12	8	65/30	0.03	.2300 X 1.3400	343
FC11004	10	4	105/30	0.03	.2700 X .8800	239
FC10804	8	4	168/30	0.03	.3650 X 1.1900	401
FC10604	6	4	259/30	0.03	.4300 X 1.4500	635

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •**  
**St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**