

Flat Speaker Wire

Flat Speaker Wire
UL Listed - 120 V



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Fully annealed 1 bare, 1 tinned stranded copper ASTM B-174

Applications:

- Hi-fi and stereo speaker wire
- Lamps
- Radios
- Suggested Voltage Rating: 120V

Category Insulation Description:

- Premium grade Polyvinyl Chloride (PVC) Color - clear Also available in black, white, brown, and gray

Standards:

- UL Wires Misc (UL 120V)

Part Number Table

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D301802	18	2	16/30	0.025	.1000 x .1870	15.9
D301602	16	2	26/30	0.025	.1120 x .2100	26
D301402	14	2	41/30	0.025	.1200 x .2300	43
D301202	12	2	65/30	0.03	.1600 x .3350	63

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •

St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC