

Solid Bare Copper

Solid Conductor
Bare Copper



*Product images are for illustrative purposes only and may differ from the actual product.

Available In:

- Soft drawn (annealed), medium hard drawn, and hard drawn

Standards:

- REA Approved
- Federal Standard QQ-W-343
- ASTM B-1 (Hard Drawn)
- ASTM B-2 (Medium Hard Drawn)
- ASTM B-3 (Soft or Annealed)
- ASTM B-33 (Tinned Soft or Annealed)

Applications:

- Used in electrical grounding systems and in overhead electrical transmission and distribution systems

Part Number Table

Part#	Gauge	Outside Diameter Inches	Material Weight (Lbs./M')	Material Weight (KG/KM)
Q11801	18	0.04	4	5
Q11601	16	0.051	8	11
Q11401	14	0.064	12	17
Q11201	12	0.081	20	29
Q11001	10	0.102	32	47
Q10801	8	0.129	50	74
Q10601	6	0.162	80	119
Q10401	4	0.204	126	187
Q10201	2	0.258	201	299
Q10101	1	0.289	253	376
Q11/001	1/0	0.325	319	474
Q12/001	2/0	0.365	403	599
Q13/001	3/0	0.41	508	755
Q14/001	4/0	0.46	641	953

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC